



This powerful and high quality drill is ideal for all general purpose drilling, honing, reaming and hole-sawing.

- Powerful motor delivers 0,37 kW (0,50 HP).
- 500 rpm free speed.
- Planetary gear reduction balances the load on bearings and gears for increased tool life.
- Professional steel chuck provides secure bit gripping.
- Ergonomic auxiliary handle provides excellent maneuverability.
- Variable-speed trigger allows easy starts.
- Through-handle exhaust directs air away from the operator.

Specifications at 6,2 bar (90 psi)

Part Number	7803A
Ordering number	80113632
Chuck capacity	1/2 in / 1,5 - 13,0 mm
Chuck type	with key
Spindle size	3/8"-24
Available versions:	
- standard chuck, reversible	7803RA
- keyless chuck, non-reversible	7803AKC
- keyless chuck, reversible	7803RAKC

PERFORMANCE

Rated power	0,50 HP / 0,37 kW
Free speed	500 rpm

AIR SYSTEM

Air Inlet (NPTF)	1/4 in
Minimum hose size	10 mm
Average air consumption	4,0 CFM / 113 L/min
Air consumption at load	27,0 CFM / 765 L/min

NOISE & VIBRATION

Sound pressure / power (ISO15744)	83,0 / 94,0 dB(A)
Vibration level / measurement uncertainty (ISO28927)	< 2,5 / - m/s ²

WEIGHT & DIMENSIONS

Tool weight	3,59 lb / 1,63 kg
Tool dimensions (L x W x H)	195 x 46 x 156 mm
Shipping weight	4,47 lb / 2,03 kg
Shipping dimensions (L x W x H)	180 x 240 x 60 mm
UPC / EAN code	6 63023 00190 6
Origin	Made in China



www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

7803A

ACCESSORIES



728-99-KC8
04276556
Keyless chuck, 13 mm



7816-99
89930770
Standard chuck, 13 mm



7816-253
89934384
Key for standard chuck, 13 mm



7803-BOOT
45524287
Protective tool boot



IB6NMC2
88103015
IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



77NMC2
88104070
7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7,2 - 7,4)



Quick Release Couplings
For the complete range, see our accessory catalogue.



Filters, regulators, lubricators
For the complete range, see our accessory catalogue.



10Z4
03875671
Oil, Class 1, no. 10, 0,12 L



Lubricants
For the complete range, see our accessory catalogue.